

ALL-POSITION PERFORMANCE.


The 104ZR Spec-2, available in size 315/80R22.5, is designed to deliver longer treadwear, improved fuel-efficiency and enhanced traction. Equipped with Yokohama's latest technology, this true workhorse is ideal for regional-haul, as well as coach/tour bus applications.

DEEP ALL-POSITION ORIGINAL TREAD




Five-Rib Full-Depth Tread Pattern

Ensures reliable handling on wet or dry roads and an exceptionally smooth and quiet ride.



Serpentine Grooves

Reduce premature shoulder step-down and irregular wear, preserving overall treadlife.



Longer Casing Life

Made possible by Zenviro technology, allows us to predict changes in tire shape that occur in early stages of wear, resulting in stabilized performance over the life of the tire and more retreads.

BUILT FOR BETTER FUEL ECONOMY



Unique Compounds

Are stronger and more pliable, improving treadwear and providing better fuel-efficiency.

SUPERIOR PROTECTION AND DURABILITY



Block-Shaped Stone Defense Rib

Prevent stones from traveling to the bottom of the grooves, reducing casing damage by 25% for greater durability and retreadability.



Ultra Wide Top Steel Belt

Increases rigidity across the entire tread, enhancing durability and preventing casing damage.



SIZES AND SPECIFICATIONS



TIRE SIZE	PART #	PLY RATING	TIRE WEIGHT	RIM SIZE		INFLATED DIMENSIONS		TREAD DEPTH	LOADED DIMENSIONS		RPM	MAX LOAD CAPACITY AT COLD INFLATION PRESSURE				MAX SPEED (KPH)
				MEASURE	ALT	OVERALL WIDTH	OVERALL DIAMETER		SECTION WIDTH	STATIC RADIUS		LB/PSI SINGLE	LB/PSI DUAL	KG/KPA SINGLE	KG/KPA DUAL	
315/80R22.5	74740	20L	149.1	9.00	9.75	12.4	42.5	21	13.6	19.6	493	9090 @ 130	8270 @ 130	4125 @ 900	3750 @ 900	120